ADESTOR DIGITAL Offset / A251 / WK80

FACESTOCK

Digital Offset

Description Calendered uncoated woodfree paper.

Ideal for all types of applications: variable label information (barcodes, expiry date, price, Applications

weight etc.)

Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional Printing techniques Suitable for printing on nexo (an types), contentions. Suitable for printing, thermal transfer, laser, hot stamping.

| Property | Norm | Units | Value | Tolerance |
|---------------------|------------|-------|-------|-----------|
| Substance | ISO 536 | g/m² | 75 | 70 - 76 |
| Thickness | ISO 534 | μm | 70 | ± 2 |
| Bekk smoothness | ISO 5627 | S | ≥ 250 | |
| Brightness ISO | ISO 2470-2 | % | 101,5 | ± 2 |
| Whiteness CIE | ISO 11475 | % | 158,2 | ± 5 |
| Opacity | ISO 2471 | % | 89 | -2 |
| Tensile strength MD | ISO 1924-2 | kN/m | 5/3 | -1 |
| | | | | |

ADHESIVE

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180º 20'/stainless steel) | FTM 1 | N/25mm | 15,4 | ≥ 12,3 |
| Shear (1kg, in²/glass) | FTM 8 | min | 100 | ≥ 60 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 10,3 | ≥ 7,8 |
| Minimum labelling temperature | | oC | 5 | |
| Minimum service temperature | | °C | -20 | |
| Maximum service temperature | | oC. | 80 | |

LINER

WK80

One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Available only in solid back

Color White

| Property | Norm | Units | Value | Tolerance |
|------------------------|------------|-------|-----------|-------------|
| Substance | ISO 536 | g/m² | 80 | ± 4% |
| Thickness | ISO 534 | μm | 81 | ± 4 |
| Tensile strength MD/CD | ISO 1924-2 | kN/m | 4,6 / 2,3 | -0,6 / -0,3 |



Certificates

Product approvals and usage certificates

FACESTOCK

Digital Offset

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper) Packaging and packaging waste Directive 94/62/CE Toy safety European directive 2009/48/CE

Electric and electronic equipment (RoHS)

ADHESIVE

A251

Packaging and packaging waste Directive 94/62/CE EN 71-3 Toy safety EN 71-9 Toy safety Direct contact with foodstuffs (ISEGA) - Adhesives

LINER

WK80

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)
Packaging and packaging waste Directive 94/62/CE
EN 71-3 Toy safety
Electric and electronic equipment (RoHS) Directive 2002/95/CE

- Values are subject to change without notice. Last updated 5/06/2016
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds ISO 9001 quality certification, ISO 14001 and EMAS environmental certifications and ISO 50001 energy management system certification. Our products are available with PEFC™ and FSC® chain of custody certificates upon request.

